

ENERGY POWER

MARKETED BY



1800 Roswell Road, Suite 2200
Marietta, GA 30062
888-823-0954

SCP SERIES VALVE REGULATED LEAD ACID BATTERY

EP-EV34-65R-X

Energy Power EV Series Batteries provide superior performance, capacities and reliability. Using state of art dry cell technology the EV series is designed for environmentally sensitive areas that require enhanced cycle life capabilities in commercial, industrial, residential, and private applications.


The maintenance free (VRLA) construction and advanced design features makes the EV Series the definitive choice for a wide variety of markets; solar and renewable energy storage; electric vehicle and golf cart; industrial equipment, floor machines, forklifts, aerial lifts, and robotics; marine, RV, and no-idle solutions; mobility and medical equipment; telecom, broadband and cable TV; UPS systems.

FEATURES AND BENEFITS

- The Energy Power, EV Battery Series along with our factories are certified to multiple standards:
 - ISO, OHSAS18001, UL, CE
 - QC/T 742-2006, GB/T18332.1-2009
- High density lead paste and specialized paste formula for deep cycle application.
- High strength ABS or PP case & cover and valve-regulated construction.
- Maintenance-free. High capacities.
- Environmentally friendly, classified as "Non-Spillable Battery" for transportation. Complies with DOT CFR 49.173.
- High tin alloy grids offer: Less gassing, High corrosion-resistant, Low self discharge, Alloy sheeting material for deep cycle applications.
- Exceptional adaptability to operate at high and low temperature environments.
- Durable copper and stainless steel terminals for high electric conductivity.
- Excellent cycle life: 80% DOD 800 cycles.
- Exclusive electrolyte formula and separator, for protecting the electrolyte density from stratification.
- Superior design allows for fast charge acceptance and resistance to over-discharge.



Deep Cycle
AGM Battery



MECHANICAL CHARACTERISTICS

Industry Type No.	35
Length(mm/inch)	259/10.2
Width (mm/inch)	169/6.6
Height(mm/inch)	174.5/6.9
Total Height(mm/inch)	177.5/7.0
Approx. Weight (kg/lbs)	19.25/42.5
Terninal	F11/M6
Container material	ABS
Cells	6 cell
Nominal Voltage	12 V

ELECTRICAL CHARACTERISTICS


Nominal Capacity	65Ah@20hour rate F. V. (1.75V/Cell)	
Internal Resistance (Approx.)	≤ Fully Charged battery (25°C) :4.9mOhms	
Self Discharge	3% of capacity per month@68°F/20°C	
Cranking Amps	460A@32°F/0°C	350A@0°F/-18°C
Max. Discharge	520A(5s)	
Reserve Capacity (80°F/27°C)	@25A F.V.(1.75V/Cell)	120 Min
	@75A F.V.(1.75V/Cell)	32Min
Charging(25°C) (Constant Voltage)	Cycle use	Initial Charging Current: 30A,2.40-2.45VPC
	Float use	2.20-2.30VPC

ELECTRICAL CHARACTERISTICS


Final voltage 1.75V/Cell	Amp Hours(AH)@77°F(25°C)						Minutes of Discharge@80°F(27°C)	
	20HR	10HR	5HR	3HR	2HR	1HR	@25A	@75A
	65	61	53.5	48.3	42.4	35.4	85	22

CHARGE / DISCHARGE TABLES & GRAPHS


CHARGE CHARACTERISTIC CURVE




CYCLE SERVICE LIFE IN RELATION TO DEPTH OF DISCHARGE




RELATIONSHIP OF OCV AND STATE OF CHARGE (25°)




SELF-DISCHARGE CHARACTERISTIC



RELATIONSHIP BETWEEN CHARGING VOLTAGE AND TEMPERATURE



TEMPERATURE EFFECTS ON CAPACITY



To ensure safe and efficient operations always refer to the latest edition of our Technical Manual, as published on our Web site. All specifications subject to change without notice.

